

CanCoverIt™



UNIVERSAL SERIES

SAFE USE WITH IC AND NON-IC RATED FIXTURES
CANCOVERIT.COM

Installs in Seconds!

Airtight Mode:


Install CanCoverIt with vents sealed when using LED or Fluorescent (Low Heat) bulbs.

Venting Mode:

NON-IC CAUTION: Install CanCoverIt with vents open when using Incandescent or Halogen (High Heat) bulbs.



Packs, ships and stores flat



Pops open
no assembly required



Air tight, durable
solution that won't
deteriorate

Fiber glass and FSK
facing will not
deteriorate over
installed life

Unique shape
controls conduction
and promotes
air circulation

Fiber glass insulates
and FSK facing
creates an air
and vapor barrier

Fiber glass is
virtually fireproof
and will not promote
mold growth

5/8" fiber glass
board and FSK
facing creates
a stable base
without flanges
or straps

Fits flush with
attic floor making
it easy to seal
with spray foam

Airtight FSK with
sealed seams
maintaining air
and vapor barrier

Easy to remove vents
allow for airtight or
vented modes
when required

Collapsible sides
enable flat shipping,
storage, and easy
maneuvering in
tight spaces

Dimensions provide
required clearance
and are sized for
optimal fit

Allows for heat
dissipation
away from
sensitive bulb
electronics

Easy to cut and
manipulate around
brackets, wires,
and framing

Made in USA

ECOCYCLESOLUTIONS™
©2013 PATENTS PENDING

More Than One Great Option...

Universal Series

SAFE USE WITH IC & NON-IC RATED FIXTURES

CANCOVERIT.COM



- External Dimensions: 14" x 14" x 22"H
- Internal Dimensions: 13" x 13" x 21½"H
- Packaged Dimensions: 14" x 2½" x 24"
- Exterior Fire Resistance Rating:
UL 723/ASTM E84 and CAN/ULC S102.
Meets NFPA 90A and 90B -
less than 25 Smoke and 50 Flame Spread
- Airflow Temp Limit: up to 250°F
- Interior Heat Resistance 475°F to 700°F
- Light Weight – Approximately 1.75 lbs
- Primary material is FSK-Faced Fiber Glass

Low Profile Series

SAFE USE WITH IC-RATED FIXTURES

CANCOVERIT.COM



- External Dimensions: 14" x 14" x 12"H
- Internal Dimensions: 13" x 13" x 11½"H
- Packaged Dimensions: 14" x 2½" x 15"
- Exterior Fire Resistance Rating:
UL 723/ASTM E84 and CAN/ULC S102.
Meets NFPA 90A and 90B -
less than 25 Smoke and 50 Flame Spread
- Airflow Temp Limit: up to 250°F
- Interior Heat Resistance 475°F to 700°F
- Light Weight – Approximately 1.25 lbs
- Primary material is FSK-Faced Fiber Glass

More Than One Reason To Use...

- Recessed Lights
- Ceiling Speakers
- Bathroom Vent Fans
- Acoustical Covers Between Floors

email: sales@cancoverit.com

phone: (949) 275-4861

Installation Videos and Instructions: www.cancoverit.com